

Roth QuickTemp Compact® FLEX FIX



Display safety data sheet



Signal word	Danger
Hazard statements	Causes skin irritation. (H315) Causes serious eye damage. (H318) May cause respiratory irritation. (H335)

General

Article no.	S796
Use of the substance / mixture	None known. PC 1 Adhesives, Sealants PROC 2 Use in closed, continuous PROC ess with occasional controlled exposure

First aid procedures

General	In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
Inhalation	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
Skin contact	IF ON SKIN: Wash with plenty of water and soap. Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
Eye contact	If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.
Ingestion	If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.
General symptoms and effects	The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.
Information for health personnel	Bring this safety data sheet or the label from this product.
Other information	Not applicable. IF exposed or concerned: Get immediate medical advice/attention.

Protective equipment

Symbols



Limitation of exposure on workplace

If possible, avoid working processes where respiratory quartz dust may be developed. Smoking, drinking and consumption of food is not allowed in the work area.

Eye protection

Safety glasses | EN166

Hand protection	Gloves > 480 EN374
Respiratory protection	S/SL P2 White EN149
Skin protection (except hands)	Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.
Other information	Ingen oksiderende egenskaper

Fire fighting measures

Suitable extinguishing media	Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.
Fire and explosion hazards	Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
Fire fighting procedures	Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Preventive Measures to contain emissions

Personal protection measures	Avoid direct contact with spilled substances. Ensure adequate ventilation, especially in confined areas. Contaminated areas may be slippery.
Environmental precautionary measures	Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill
Cleaning method	Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust. Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

Responsible company

Company name	Roth North Europe AS Frederikssund
--------------	---------------------------------------