

Roth Compact® Primer

Description

Roth Compact® Primer is a cement-based, fibre-reinforced, highly flexible primer that ensures good adhesion between Roth Compact® systems.

Technical description

Water to be added:	2.5 L water per 10 kg
Mixing time:	2 minutes
Quantity needed:	1.0 - 1.5 kg/m ²
Laying thickness:	1 mm
Drying time:	3 hours at +18°C and 50% RH
Application temperature:	+6 - +25°C.
Consistency:	Partially liquid
Adhesion to aluminium:	> 1.0 MPa
Processing time:	20 minutes
Walkability:	Approx. 3 hours



Storage

Store in a dry place. Should be used within 12 months of the production date.

UK No. 7339349810

WARNING

Cement!

Causes skin irritation.

Causes serious eye irritation.

May cause irritation of the respiratory tract.

Do not inhale the powder.

Wear protective gloves/protective clothing/eye protection/face protection.

In the event of contact with the eyes: Rinse gently with water for several minutes.

Remove any contact lenses if this can be done easily. Continue rinsing.

If eye irritation persists: Seek medical attention.

Repeated contact may cause dry or cracked skin.

The product is not classified as hazardous waste. Spillage and pollution should be avoided. The contents/packaging are to be disposed of using an approved waste system in accordance with any local authority requirements.

KEEP OUT OF REACH OF CHILDREN.