

## Roth Minishunt Plus cabinet

### Roth Minishunt Plus Cabinet 437 x 475 x 108 mm

Roth Minishunt Plus cabinet, is a banded underfloor heating cabinet that houses control, duo distributor and Roth Minishunt Plus. The cabinet is adapted for installation recessed into a wall.

The fixing of the Minishunt Plus and accessories are possible both vertically and horizontally for easy mounting. The cabinets are supplied with Roth pipe penetrations that can be used for all kinds of smooth pipes and protective pipes in dimensions 10 - 34 mm.

The bushes are split by hand to the correct dimensions and are internally lubricated from the factory to facilitate assembly of the pipes. If the bushings are to be used against protective pipes, they must be supplemented with Roth strain relief for empty pipes 20 - 28 mm or 25 - 34 mm.

The waterproof cabinets meet the requirements for Safe Water installation if the installation instructions and industry rules are followed. The cabinet is tested and approved according to NT VVS 129, which means that the cabinet can also be used for tap water installations.

#### Technical description

Roth Minishunt Plus cabinets are made of sheet metal that is pretreated with Oxsilan technology, an environmentally friendly corrosion protection.

The cabinet is powder coated in the color White RAL 9010.

Other details in the cabinet are made of galvanized steel. When the cabinet is installed recessed into a wall, the installation depth is 108 mm, with the door and frame mounted, the depth inside the cabinet is 127 mm.

The cabinets are supplied with pipe penetrations 10 - 34 mm made of EPDM, as well as Roth QuickBox® leak indication (see separate installation instructions).

#### Area of use

> Underfloor heating systems



# Roth Minishunt Plus cabinet

## Technical data

Roth Minishunt Plus cabinet

SAP nr. 17SF1000.131

## Accessories

Roth adapter for Minishunt Plus

Roth duo distributor, kit

Roth coupling 10,5 x 1,3 mm GE20 RG

Roth coupling 16 x 2,0 mm GE20 RG

Roth coupling 20 x 2,0 mm GE20 RG

SAP no. 170T1000.000

SAP no. 17046296.220

SAP no. 17401974.810

SAP no. 17401975.816

SAP no. 17401975.820

B	H	D	Installation depth	No. of pipe holes	Weight
350 mm	419 mm	108 mm	108 mm	8	8,2 kg

