

# Roth Touchline® PL Controller 2 Ch

### Wireless control system for underfloor heating

Roth Touchline® PL control system is used for regulation of the room temperature in 2 rooms with underfloor heating where a simple but well-functioning system is needed.

The system consists of a 2 channel controller connected with up to 2 wireless room thermostats.

The box has no control panel as this is not needed when pairing the thermostat. The thermostats are available in 2 variants: Roth Touchline® SL Standard and Roth Touchline® PL. Both thermostats have a display and touch buttons.

# **Room thermostats**

# Roth Touchline® PL room thermostat

The thermostat comes in white with a smaller LCD display protected by a transparent polycarbonate plate. The power supply is 2 x AAA 1.5V batteries. The temperature is easily set with the two touch buttons (+/-). It is also possible to lock the buttons for accidental operation.

The following menues are available in the thermostats: Battery status, calibrating, key lock, factory reset, continous temperature.

#### Roth Touchline® SL Standard room thermostat

The thermostat comes in white with a bigger LCD display. The front is protected by a transparent polycarbonate plate. The power supply is 2 x AAA 1.5V batteries.

The temperature is easily set with the two touch buttons (+/-). It is possible to switch between room temperature and room humitity level using the middle button. It is also possible to lock the buttons for accidental operation.

The following menues are available in the thermostats: Battery status, key lock and factory reset.

### **Control box**

The control box is a 2 channel controller. The box can be mounted directly on the wall. The controller has 230V output for 4 actuators (max. 2 pr. channel). Furthermore it has 230V output for pump.

Individual LED indicators on the front shows the status of the outputs.

# First start-up

When first starting up an underfloor heating system, an actuator should be fully opened to ensure proper operation, it is also important to get all air flushed out of the system.

### Dumn run

To extend the durability of the pump and ensure that the pump does not get stuck, the system automatically performs Pump run every 10 days for 5 minutes.



# Valve health check

Long durability and securing of valve and the function of the operation is ensured by the automatic valve and actuator exercise which is performed every 10 days for 5 minutes.

### Sections of functionality

- > Up to 30 m indoor range
- > Locking the thermostat for public use
- > On/Off regulation
- > To be used for underfloor heating
- Control of pump and actuators



# Roth Touchline® PL Controller 2 Ch

HVAC no. 7466397752

230V AC

2 outputs for

 $(4 \times 0.3 A)$ 

(EN60730)

Up to) 30 m (ordinary building)

230V and 0.5 A

868 MHz

150 cm

5 - 50°C

< 80% RH

-20 - +50°C

(EN60529)

(5 x 20mm)

HVAC no. 7466397100

HVAC no. 7466397180

HVAC no. 7466397181

2 pcs. AAA 1.5V

> 2 years

~ 50uA

0.5 K.

< 2 sec.

10 sec.

Max. 5 sec.

up to 30 m

Max. 80% RF

(EN60529)

CE, UKCA

(ordinary building)

868 MHz

0 - 55°C

+5 - +35°C

Approx. 4 min.

CE, UKCA

actuators (NC), 230V AC 4 thermal motors

4W

## Controller

Roth Touchline® PL Controller 2 channel Supply voltage Energy consumption Number of outputs and voltage

Trainber of outputs and voltag

Max. sustained load

Protection class I Transmission frequency

Range

Max. load pump relay Power supply cable Ambient temperature Ambient humidity Storage/transport temperature Degree of protection IP20 Fuse glass fuse WT 6.3A Certificate

#### **Thermostats**

Roth Touchline® PL room thermostat Roth Touchline® SL Standard room thermostat, white Roth Touchline® SL Standard room thermostat, black Supply voltage Battery life Power consumption standby Room temperature, setting range Accuracy (resolution) Time constant (time delay) Activation time (wake-up time) Max. forced update time for data from control box Standby display without operation Transmission frequency

Ambient temperature Ambient humidity Degree of protection IP20 Certificate

# **Accesories**

Range

Roth Touchline® PL actuator 230V HVAC no. 7466275430 Roth Touchline® actuator 230V, NC, 1W HVAC no. 7466275433

### Roth Touchline® PL Controller 2 channels complete set


HVAC no. 7466397772

1 pcs Roth Touchline® PL Controller 2 channels


2 pcs Roth Touchline® SL Standard white room thermostats and

2 pcs Roth Touchline® actuators


# Roth Touchline® PL Controller



### Roth Touchline® PL room thermostat



# Roth Touchline® SL Standard room thermostat



## **Connections to controller**

