


Roth Touchline® SL 4 ch, extension module

Roth Touchline® SL 4 ch, extension module

The Roth Touchline® SL 4 ch extension can be connected to both Roth Touchline® SL Controller 8 ch master or 8 ch extension.

The Roth Touchline® SL 4 ch extension is connected using the included 0,5 m BUS cable. If there are very large distances between the controllers, you can choose to connect all the units using a BUS cable instead. For this setup we refer to the user manual which is online on our website.



Technical data

Roth Touchline® SL 4 ch, extension module

	HVAC no. 7466397064
Supply voltage	230V AC
Energy consumption	3 W
Number of outputs and voltage	9 (NC/NO), 230V AC
Max. sustained load (0.3A)	9 thermal actuators
	(3 outputs with 2 actuators and 1 output with 3 actuators)
Wireless channels (per zone)	4 thermostat/sensors 6 radiator actuators
(per zone)	6 window contacts
Protection class I	(EN60730)
Power supply cable	85 cm
Ambient temperature	5 - 50°C
Ambient humidity	< 80% RH
Storage / transport temperature	-20 - +50°C
Degree of protection	IP20 (EN60529)
Fuse glass fuse	WT 3.15A (5 x 20 mm)
Approvals	CE 2014/53/EU

