

Roth Touchline® SL Controller, extension

Roth Touchline® SL Controller, extension

One Roth Touchline® SL 8 ch Controller, master can be connected wireless to up to 3 pc. Roth Touchline® SL 8 ch Controller, extension.

In addition, each controller can be connected to 1 pc. 4 channel extension with BUS cable, i.e. up to 48 channels in a system. If there are very large distances between the controllers, you can choose to connect the units using a BUS cable instead.



Technical data

Roth Touchline® SL Controller, extension

8 ch 230V

Supply voltage

Energy consumption

Number of outputs and voltage

Max. sustained load

HVAC no.7466397068

230V AC

6 W

19 (NC/NO), 230V AC

19 thermal actuators (0.3A)

(3 outputs with 3 actuators and 5 outputs with 2 actuators)

8 thermostat/sensors

6 radiator actuators (per zone)

6 window contacts (per zone)

(EN60730)

Wireless channels

Protection class I

Transmission frequency

Range (up to)

868 MHz

30 m (in ordinary building)

Wired BUS connection

Max. load pump relay

Max. load potential-free relay

Power supply cable

Ambient temperature

Ambient humidity

Storage/transport temperature

Degree of protection

Fuse glass fuse

Approvals

RS485 (max. 100 m)

230V and 0.5 A

1A

85 cm

5 - 50°C

< 80% RH

-20 - +50°C

IP20 (EN60529)

WT 6.3A (5 x 20 mm)

CE 2014/53/EU

