

# Roth Touchline® SL radiator actuator

The Roth Touchline® SL radiator actuator is used in conjunction with the Roth Touchline® SL control system to connect with radiator systems.

## Description

The Roth Touchline® SL radiator actuator is intended for use with the Roth Touchline® SL control system and makes it possible to control your radiator valves wireless in combination with a room thermostat or room sensor. Connecting nut on the actuator is M30x1,5 and can be used directly on Roth's own valves and floor heating manifolds. The actuator can also be used directly on valves from IMI/Heimeier TRV3 and Honeywell radiator valves. Adapters for Danfoss type RAN and type RTD-N are included. The radiator actuator has a built in function called SIGMA which secures an optimal control of the actuator and best use of the batteries.



## Technical data

Roth Touchline® SL radiator actuator	HVAC No. 7466397450
Supply voltage	2 x AA 1,5V battery
Expected battery life	> 2 years
Protection class I	(NA)
Transmission frequency	> 868 MHz
Ambient temperature	-30 - +50°C
Ambient humidity	< 90% RF
Temperature Storage/transport	-25 - +50°C
Degree of protection	IP61
Approvals CE	2014/53/EU
Connecting nut	M30x1,5
Adapters incl.	Danfoss RAN og RTD-N

## Roth Touchline® SL radiator actuator

