

# Roth Touchline® SL repeater

The Roth Touchline® SL repeater can be used for a range of Roth products, Roth Touchline® SL, Roth Touchline® PL, Roth wireless control for Minishunt Plus and Roth QuickStop Sensor 2.

## Description

The Roth Touchline® SL repeater is intended to be used as signal amplifier in the Roth Touchline® SL system. Roth Touchline® SL repeater can be used if there are problems with the signal between thermostats, sensors, smart accessories and controller or between master controller and extension module.

The repeater can handle up to 20 devices.

## Technical data

|  |                                 |
|--|---------------------------------|
| Roth Touchline® SL repeater            | HVAC nr. 7466397400             |
| Supply voltage                         | 230V ~ 50Hz                     |
| Maximum power consumption              | < 1W                            |
| Max. transmission power                | 25mW                            |
| Protection class                       | II                              |
| Transmission Ambient                   | 868 MHz                         |
| Ambient temperature                    | +5°C - +50°C                    |
| Ambient Humidity                       | < 80% RF                        |
| Degree of protection                   | IP20                            |
| Approvals CE                           | 2014/53/EU,29/125/EC,2011/65/EU |
| Transmission range Controller/Repeater | 50 m                            |



## Roth Touchline® SL repeater

